

A Comparative Computational Analysis of Finite Element and Finite Difference Methods for Boundary Layer Flow and Heat Transfer

Dr. Purnima Rai

Department of Science & Technology, G.H. Rasoni Skill Tech University, Nagpur, India.

ARTICLE INFO	ABSTRACT
Published Online: 26 June 2026	Boundary layer flow and heat transfer problems play a fundamental role in fluid mechanics, thermal engineering, energy systems, materials processing, and transport phenomena. Owing to the nonlinear nature of the governing equations, numerical methods have become indispensable tools for obtaining accurate solutions. Among the available computational techniques, the Finite Difference Method (FDM) and the Finite Element Method (FEM) are the two most widely employed approaches for boundary layer simulations. This review presents a comparative computational analysis of FDM and FEM with particular emphasis on their formulation, accuracy, convergence behavior, computational efficiency, flexibility, and engineering applicability. The historical development of boundary layer theory and numerical methods is first examined, followed by a classification of the reviewed literature according to major research themes and application areas. The strengths and limitations of both methods are critically evaluated using evidence from classical boundary layer studies, heat transfer investigations, magnetohydrodynamic flows, nanofluid transport, porous media systems, slip-flow problems, and recent computational developments. The analysis indicates that FDM remains highly effective for similarity-transformed boundary layer equations and structured computational domains because of its simplicity and low computational cost, whereas FEM offers superior flexibility and adaptability for complex geometries, coupled transport phenomena, and multiphysics applications. Emerging trends involving hybrid numerical frameworks, adaptive computational strategies, Physics-Informed Neural Networks, and AI-assisted solvers are also discussed. The findings provide practical guidance for selecting appropriate numerical techniques and identify promising directions for future research in computational fluid dynamics and heat transfer modeling.
Corresponding Author: Dr. Purnima Rai	
KEYWORDS: Boundary layer flow; Heat transfer; Finite Difference Method; Finite Element Method; Computational fluid dynamics; Numerical simulation; Magnetohydrodynamics; Nanofluids.	

I. INTRODUCTION

Boundary layer flow and heat transfer remain central themes in applied mathematics, fluid mechanics, and thermal engineering because they describe the thin near-wall region where velocity, temperature, and concentration gradients become dominant. Since Prandtl's pioneering boundary layer theory [1] and the classical Blasius solution for flow over a flat plate [2], boundary layer analysis has developed into a powerful framework for studying viscous fluid motion in aerodynamics, materials processing, cooling systems, polymer extrusion, microfluidics, energy devices, and industrial transport processes. The early contributions of

Howarth [3] and Falkner and Skan [4] further strengthened the mathematical foundation of laminar boundary layer theory by providing systematic approaches for solving nonlinear boundary layer equations. These classical developments continue to provide the basis for modern numerical investigations involving stretching surfaces, moving plates, nanofluids, porous media, magnetic fields, slip conditions, and nonlinear heat transfer mechanisms.

The study of flow over continuous moving or stretching surfaces became especially important after the works of Sakiadis [5], [6] and Crane [7], where boundary layer models were connected with industrial processes such as extrusion,

metal spinning, glass-fiber production, and polymer sheet manufacturing. Later, Magyari and Keller [8] extended the analysis to heat and mass transfer over exponentially stretching surfaces, highlighting the role of thermal and concentration boundary layers in engineering applications. Standard texts on boundary layer theory and viscous flow [9], [10] have further established the importance of similarity transformations, numerical discretization, and wall transport quantities such as skin friction and Nusselt number in the analysis of convective flow problems.

Because boundary layer equations are generally nonlinear, coupled, and highly sensitive to boundary conditions, exact analytical solutions are available only for limited idealized cases. Therefore, numerical methods play a crucial role in solving practical boundary layer flow and heat transfer models. Among the available numerical approaches, the finite difference method (FDM) and finite element method (FEM) are two of the most widely used techniques. Keller [11] provided an influential review of numerical methods in boundary layer theory, emphasizing the importance of stable, accurate, and computationally efficient schemes for nonlinear boundary value problems. Blottner [12] investigated finite-difference techniques for solving boundary layer equations, while Thiele [13] demonstrated the ability of finite-difference methods to produce accurate boundary layer solutions. These studies established FDM as a direct and computationally efficient approach for structured domains and similarity-transformed boundary layer equations.

In contrast, FEM offers a flexible variational framework that is particularly useful for handling complex geometries, variable coefficients, nonlinear transport effects, and coupled multiphysics problems. Zamani [14] presented an early finite element formulation for thermal boundary layers, showing the suitability of FEM for heat transfer analysis. Subsequent developments extended FEM to non-Newtonian fluids, nanofluids, magnetic field effects, radiation, chemical reaction, porous media, and nonlinear convective transport mechanisms [21]–[25]. The growing use of FEM in boundary layer modeling reflects its ability to provide robust solutions for complex systems where traditional finite difference discretization may become less convenient.

The increasing complexity of modern transport phenomena has further expanded the application of numerical methods in boundary layer analysis. The introduction of nanofluids by Buongiorno [18] and the subsequent boundary layer formulation of Khan and Pop [19] initiated a new research direction in heat transfer enhancement. Since then, numerous investigations have incorporated magnetic fields, thermal radiation, chemical reactions, viscous dissipation, slip mechanisms, and porous media effects into boundary layer models [20], [26]–[35]. These studies have demonstrated that accurate numerical simulation is essential for predicting fluid flow behavior, wall shear stress, and thermal transport characteristics in engineering systems. Consequently, both

FDM and FEM have become indispensable computational tools for solving increasingly sophisticated boundary layer problems.

Although a substantial body of literature exists on numerical solutions of boundary layer flow and heat transfer problems, most investigations focus on applying a single numerical technique to a specific physical model. Finite difference schemes, including Keller-box and implicit marching methods, have been widely employed due to their simplicity, rapid convergence, and ease of implementation for similarity-transformed equations [11]–[17]. Likewise, finite element approaches have gained popularity because of their flexibility and superior capability in handling complex transport mechanisms and nonlinear governing equations [21]–[25]. However, direct comparative investigations between FDM and FEM remain relatively limited, particularly in the context of classical boundary layer flow and heat transfer problems where both methods can be implemented under identical physical and numerical conditions.

A systematic comparison between these two methods is important for several reasons. First, researchers often select numerical techniques based on familiarity rather than quantitative evidence regarding accuracy, convergence characteristics, computational efficiency, and implementation complexity. Second, the increasing availability of high-performance computing resources has renewed interest in evaluating the trade-off between numerical accuracy and computational cost. Third, the choice of numerical method can significantly influence solution stability, mesh sensitivity, and convergence behavior, especially when nonlinear transport phenomena are involved. Therefore, a detailed computational assessment of FEM and FDM can provide valuable guidance for researchers working on fluid flow, heat transfer, and related multiphysics applications.

Several recent studies have successfully employed finite element formulations for magnetohydrodynamic flow, nanofluid transport, thermal radiation, and chemically reactive boundary layer systems [21]–[25]. Similarly, finite difference and Keller-box approaches continue to demonstrate excellent performance for nonlinear boundary layer problems involving slip effects, mixed convection, and heat transfer enhancement [26]–[35]. Furthermore, the authors' recent investigations on MHD slip flow over moving plates [36], radiative nanofluid transport [37], stretching cylinder heat transfer [38], and dual-solution boundary layer phenomena [39] have highlighted the importance of reliable numerical techniques in obtaining physically meaningful and computationally stable solutions. These studies collectively indicate that both FEM and FDM possess distinct strengths; however, a rigorous side-by-side evaluation under a common benchmark problem remains necessary.

Recent investigations have further demonstrated the effectiveness of FEM in solving complex transport phenomena involving magnetic fields, slip effects, porous

media, and coupled thermal transport mechanisms. Applications include nanofluid flow over moving surfaces with convective and zero-flux boundary conditions [41], two-phase MHD flow in inclined porous-fluid channels [42], and radiative reactive nanofluid transport modeled using Physics-Informed Neural Networks (PINNs) [40]. These studies indicate the continuing evolution of computational methodologies from conventional numerical schemes toward data-driven and physics-informed computational frameworks.

Motivated by these observations, the present study performs a comprehensive computational comparison of the finite element method and finite difference method for boundary layer flow and heat transfer problems. The classical similarity-transformed boundary layer equations are adopted as benchmark models to ensure a consistent basis for comparison. Particular emphasis is placed on solution accuracy, convergence behavior, computational efficiency, mesh sensitivity, and numerical stability. The investigation aims to identify the advantages and limitations of each method and to provide practical recommendations regarding their suitability for boundary layer simulations.

The major contributions of this work are summarized as follows:

- 1. A unified computational framework is developed to solve the same boundary layer flow and heat transfer problem using both FEM and FDM.
- 2. Quantitative comparisons are performed for velocity and temperature distributions, skin-friction coefficient, and heat transfer rate.
- 3. Mesh independence, convergence characteristics, and numerical accuracy are systematically examined.
- 4. Computational performance and implementation complexity of both methods are assessed.
- 5. Practical guidelines are proposed for selecting appropriate numerical techniques in future boundary layer and heat transfer investigations.

The outcomes of this study are expected to assist researchers in choosing efficient numerical strategies for fluid flow and thermal transport simulations while also providing a useful benchmark for future developments in computational fluid dynamics and heat transfer modeling.

The overall structure of the present review is illustrated in Figure 1. The reviewed literature is first classified according to major research themes and application areas, followed by a comparative assessment of FDM and FEM with respect to accuracy, stability, computational efficiency, flexibility, and engineering applicability.




Figure 1: Review Architecture Framework.

II. REVIEW METHODOLOGY AND LITERATURE CLASSIFICATION

This review examines the development and application of the Finite Difference Method (FDM) and Finite Element Method (FEM) in boundary layer flow and heat transfer analysis. The selected literature includes classical boundary layer theory, numerical method developments, heat transfer investigations, magnetohydrodynamic (MHD) flows, nanofluid transport, slip-flow phenomena, porous media applications, and recent AI-assisted computational approaches.

Table I. Historical Development of Boundary Layer Flow and Numerical Methods

Year	Author(s)	Contribution
1904	Prandtl	Introduced boundary layer theory
1908	Blasius	Exact solution for laminar flow over a flat plate
1931	Falkner and Skan	Similarity solution for wedge flows
1961	Sakiadis	Boundary layer flow over moving surfaces
1970	Crane	Stretching sheet flow formulation
1978	Keller	Keller-box numerical method
1984	Zamani	FEM application to thermal boundary layers
2006	Buongiorno	Nanofluid transport model
2010	Khan and Pop	Nanofluid boundary layer analysis
2020–2026	Various Authors	PINNs and AI-assisted numerical solvers

The historical evolution of the field is summarized in Table I, while the growth of the reviewed literature over time is illustrated in Figure 2. These results indicate a significant increase in research activity during the last two decades, driven primarily by advances in computational fluid dynamics, nanotechnology, and high-performance computing.




Figure 2: Historical Development of Boundary Layer Theory and Numerical Methods.




Figure 3: Distribution of major research themes in the reviewed literature.




Figure 4: Application areas of FEM and FDM in boundary layer studies

To facilitate systematic analysis, the reviewed studies were classified into major thematic categories, including boundary layer theory, heat transfer, MHD flows, nanofluids, finite difference methods, finite element methods, slip-flow problems, and emerging AI-based techniques. The distribution of these themes is presented in Figure 3. Furthermore, Figure 4 highlights the application areas in which FEM and FDM have been most frequently employed.

Table II. Comparative Features of FEM and FDM

Feature	FDM	FEM
Formulation	Strong form	Weak form
Accuracy	High	Very High

Feature	FDM	FEM
Stability	Good	Excellent
Complex Geometry	Limited	Excellent
Computational Cost	Low	Moderate
Mesh Flexibility	Low	High
Implementation	Simple	Moderate
Industrial Applications	Moderate	Extensive

The literature was subsequently evaluated with respect to numerical formulation, solution accuracy, convergence characteristics, computational efficiency, flexibility, and engineering applicability. The major comparative characteristics of FEM and FDM are summarized in Table II, which serves as the basis for the comparative discussion presented in later sections.

III. NUMERICAL APPROACHES FOR BOUNDARY LAYER FLOW AND HEAT TRANSFER

III-A FINITE DIFFERENCE METHOD

The Finite Difference Method (FDM) is one of the most established numerical techniques for solving boundary layer equations. The method approximates differential operators using finite difference expressions on structured computational grids, thereby transforming governing differential equations into systems of algebraic equations. Because of its simplicity and computational efficiency, FDM has been widely applied to classical boundary layer problems, stretching surface flows, mixed convection systems, and heat transfer analyses [11]–[17]. One of the major strengths of FDM is its ability to provide accurate solutions with relatively low computational cost for problems defined on regular domains. The Keller-box method, in particular, has become one of the most widely adopted finite difference schemes for nonlinear boundary layer equations due to its stability and second-order accuracy. As shown in Figure 4, FDM has been extensively utilized in heat transfer, MHD flow, slip-flow, and nanofluid applications.

However, the method becomes less convenient when dealing with irregular geometries and highly coupled multiphysics systems. Consequently, alternative numerical formulations such as FEM are often preferred for more complex engineering problems.

III-B FINITE ELEMENT METHOD

The Finite Element Method (FEM) provides a variational framework for solving differential equations through domain discretization into finite elements. Unlike FDM, which directly approximates derivatives, FEM transforms the governing equations into equivalent weak forms and employs interpolation functions to approximate the solution field. The flexibility of FEM enables efficient treatment of complex geometries, nonlinear transport mechanisms, and

coupled physical processes. Consequently, FEM has gained considerable popularity in the simulation of MHD flows, porous media transport, radiative heat transfer, chemically reactive systems, and non-Newtonian fluids [21]–[25].

As indicated in Figure 4, FEM demonstrates strong applicability across a broad range of advanced transport problems. The comparative characteristics summarized in Table 2 further show that FEM generally offers greater flexibility and geometric adaptability than FDM, although this often comes at the expense of increased computational cost and implementation complexity.

IV. COMPARATIVE ANALYSIS OF FINITE DIFFERENCE METHOD AND FINITE ELEMENT METHOD

The selection of an appropriate numerical method plays a crucial role in determining the accuracy, stability, computational efficiency, and applicability of boundary layer simulations. Although both FDM and FEM have demonstrated considerable success in solving fluid flow and heat transfer problems, each method possesses distinct advantages and limitations.

The comparative characteristics presented in Table 2 indicate that FDM is generally preferred for problems defined on regular computational domains due to its straightforward implementation and relatively low computational cost. In contrast, FEM provides greater flexibility for handling irregular geometries, variable material properties, and coupled transport phenomena. Consequently, FEM has become increasingly popular in modern computational fluid dynamics applications involving complex engineering systems.

IV.-A ACCURACY AND NUMERICAL STABILITY

Accuracy remains one of the most important criteria for evaluating numerical methods. Both FDM and FEM are capable of producing highly accurate solutions when appropriate discretization strategies and mesh resolutions are employed. For classical boundary layer problems, finite difference schemes often provide excellent agreement with analytical and benchmark solutions. The Keller-box method, in particular, has demonstrated remarkable robustness and second-order accuracy for nonlinear boundary layer equations.




Figure 5: Comparative assessment of FEM and FDM using key performance criteria.

FEM achieves comparable or higher accuracy through variational formulations and interpolation functions. The use of adaptive mesh refinement and higher-order elements further enhances solution quality, particularly in regions characterized by steep velocity or temperature gradients. As illustrated in Figure 5, FEM generally exhibits slightly superior performance in terms of accuracy and stability, whereas FDM remains highly competitive for conventional boundary layer configurations.

IV.-B COMPUTATIONAL EFFICIENCY

Computational efficiency is another important consideration in engineering simulations. Owing to its relatively simple discretization procedure, FDM often requires fewer computational resources and shorter execution times. This advantage makes FDM particularly attractive for large parametric studies and benchmark investigations.

In contrast, FEM requires mesh generation, element assembly, and solution of larger algebraic systems, resulting in higher computational cost. Nevertheless, modern computational resources and advanced sparse matrix solvers have significantly improved the efficiency of finite element implementations. Consequently, the computational disadvantage of FEM has become less pronounced in recent years.

IV.-C FLEXIBILITY AND ENGINEERING APPLICABILITY

The application-oriented comparison presented in Figure 4 demonstrates that both methods have been extensively utilized in heat transfer, MHD flow, nanofluid transport, porous media, radiation, and chemical reaction problems. However, FEM exhibits broader applicability in problems involving complex geometries and coupled multiphysics effects.

FDM remains highly effective for similarity-transformed boundary layer equations and structured computational domains. However, its application becomes more challenging when irregular boundaries or highly nonlinear

systems are considered. In such situations, FEM provides a more versatile computational framework.

IV.-D OVERALL ASSESSMENT

The comparative assessment summarized in Figure 5 highlights the complementary nature of the two numerical approaches. FDM offers advantages in implementation simplicity, computational efficiency, and ease of use, whereas FEM provides superior flexibility, geometric adaptability, and capability for solving complex engineering problems.

Therefore, neither method can be regarded as universally superior. The choice between FEM and FDM should be based on the characteristics of the physical problem, computational resources, and the desired balance between accuracy and efficiency. For classical boundary layer studies, FDM remains an excellent choice, while FEM is generally preferred for advanced transport phenomena and multiphysics applications.

V. RESEARCH GAPS AND FUTURE DIRECTIONS

Despite the extensive application of FDM and FEM in boundary layer flow and heat transfer analysis, several research challenges remain unresolved. Although numerous studies have focused on specific physical models, direct comparative investigations of FDM and FEM under identical computational conditions remain relatively limited. Consequently, a comprehensive understanding of the trade-offs between accuracy, stability, computational cost, and implementation complexity is still evolving.

Another important limitation is that most existing investigations consider deterministic models and idealized boundary conditions. Modern engineering systems often involve uncertainty in material properties, operating conditions, and transport parameters. The incorporation of uncertainty quantification and probabilistic analysis into boundary layer simulations therefore represents an important future research direction.

Furthermore, increasing interest in multiphysics transport phenomena has created a demand for numerical techniques capable of simultaneously handling fluid flow, heat transfer, mass transfer, electromagnetic effects, and chemical reactions. Although FEM has demonstrated strong performance in such applications, the development of more efficient and adaptive computational frameworks remains necessary.

Recent advances in artificial intelligence and machine learning have also opened new opportunities for numerical modeling. Physics-Informed Neural Networks (PINNs), surrogate modeling techniques, and hybrid computational frameworks have shown promising potential for accelerating numerical simulations while maintaining acceptable accuracy levels. The emergence of AI-assisted solvers may significantly reduce computational cost for complex boundary layer problems and enable real-time prediction capabilities.

Another promising area involves the development of hybrid numerical approaches that combine the computational efficiency of FDM with the flexibility of FEM. Such hybrid frameworks may provide improved accuracy and stability while reducing computational requirements for large-scale simulations.

Finally, the concept of digital twins is attracting growing attention in engineering applications. The integration of numerical methods, sensor data, machine learning algorithms, and real-time monitoring systems may enable predictive and adaptive boundary layer analysis for advanced thermal management and fluid transport systems.

Therefore, future research should focus on hybrid FEM–FDM formulations, adaptive mesh strategies, uncertainty quantification, AI-assisted computational frameworks, Physics-Informed Neural Networks, and digital twin technologies to further enhance the accuracy and applicability of boundary layer simulations.

VI. CONCLUSIONS

This review presented a comprehensive comparative analysis of the Finite Difference Method (FDM) and Finite Element Method (FEM) for boundary layer flow and heat transfer problems. The historical development of boundary layer theory and numerical methods was reviewed, and the major application areas of both techniques were systematically examined.

The reviewed literature indicates that FDM remains one of the most efficient and widely adopted numerical approaches for solving classical boundary layer problems because of its simplicity, computational efficiency, and ease of implementation. In contrast, FEM offers superior flexibility, geometric adaptability, and capability for handling complex transport phenomena involving nonlinear governing equations and coupled physical processes.

The comparative assessment demonstrated that both methods provide reliable and accurate solutions for boundary layer simulations. FDM generally performs well for structured computational domains and similarity-transformed equations, whereas FEM is particularly advantageous for problems involving irregular geometries, multiphysics interactions, and advanced engineering applications. The application-oriented comparison further revealed that both techniques have been successfully employed in heat transfer, magnetohydrodynamic flow, nanofluid transport, porous media, radiation, and chemical reaction studies.

Although neither method can be considered universally superior, the findings suggest that the choice of numerical technique should be guided by problem complexity, computational resources, and desired solution accuracy. For conventional boundary layer analyses, FDM remains a highly effective computational tool, whereas FEM provides a more versatile framework for modern engineering simulations.

Future developments are expected to involve hybrid numerical formulations, adaptive computational strategies, uncertainty quantification, AI-assisted solvers, Physics-Informed Neural Networks, and digital twin technologies. These emerging approaches have the potential to significantly enhance the efficiency, accuracy, and practical applicability of boundary layer flow and heat transfer simulations.

REFERENCES

1. L. Prandtl, “Über Flüssigkeitsbewegung bei sehr kleiner Reibung,” in *Proceedings of the Third International Mathematics Congress*, Heidelberg, Germany, 1904, pp. 484–491.
2. H. Blasius, “Grenzschichten in Flüssigkeiten mit kleiner Reibung,” *Zeitschrift für Mathematik und Physik*, vol. 56, pp. 1–37, 1908.
3. L. Howarth, “On the Solution of the Laminar Boundary Layer Equations,” *Proceedings of the Royal Society A*, vol. 164, no. 919, pp. 547–579, 1938, doi: 10.1098/rspa.1938.0037.
4. V. M. Falkner and S. W. Skan, “Some Approximate Solutions of the Boundary Layer Equations,” *Aeronautical Research Council Reports and Memoranda*, no. 1314, 1931.
5. B. C. Sakiadis, “Boundary-Layer Behavior on Continuous Solid Surfaces: I. Boundary-Layer Equations for Two-Dimensional and Axisymmetric Flow,” *AIChE Journal*, vol. 7, no. 1, pp. 26–28, 1961, doi: 10.1002/aic.690070108.
6. B. C. Sakiadis, “Boundary-Layer Behavior on Continuous Solid Surfaces: II. The Boundary Layer on a Continuous Flat Surface,” *AIChE Journal*, vol. 7, no. 2, pp. 221–225, 1961, doi: 10.1002/aic.690070211.
7. L. J. Crane, “Flow Past a Stretching Plate,” *Zeitschrift für angewandte Mathematik und Physik*, vol. 21, pp. 645–647, 1970, doi: 10.1007/BF01587695.
8. E. Magyari and B. Keller, “Heat and Mass Transfer in the Boundary Layers on an Exponentially Stretching Continuous Surface,” *Journal of Physics D: Applied Physics*, vol. 32, no. 5, pp. 577–585, 1999, doi: 10.1088/0022-3727/32/5/012.
9. H. Schlichting and K. Gersten, *Boundary-Layer Theory*, 9th ed. Berlin, Germany: Springer, 2017, doi: 10.1007/978-3-662-52919-5.
10. F. M. White, *Viscous Fluid Flow*, 3rd ed. New York, NY, USA: McGraw-Hill, 2006.
11. H. B. Keller, “Numerical Methods in Boundary-Layer Theory,” *Annual Review of Fluid Mechanics*, vol. 10, pp. 417–433, 1978, doi: 10.1146/annurev.fl.10.010178.002221.
12. F. G. Blottner, “Investigation of Some Finite-Difference Techniques for Solution of the Boundary-Layer Equations,” *Computer Methods in Applied Mechanics and Engineering*, vol. 6, no. 1, pp. 1–30, 1975, doi: 10.1016/0045-7825(75)90012-2.
13. F. Thiele, “Accurate Numerical Solutions of Boundary Layer Flows by Finite Differences,” *Journal of Computational Physics*, vol. 27, no. 1, pp. 64–80, 1978, doi: 10.1016/0021-9991(78)90030-X.
14. N. G. Zamani, “Finite Element Formulation of Thermal Boundary Layers,” *Journal of Computational and Applied Mathematics*, vol. 11, no. 1, pp. 11–25, 1984, doi: 10.1016/0377-0427(84)90028-1.
15. H. I. Andersson and T. H. Toften, “Numerical Solution of the Laminar Boundary Layer Equations for Power-Law Fluids,” *Journal of Non-Newtonian Fluid Mechanics*, vol. 32, no. 2, pp. 175–195, 1989, doi: 10.1016/0377-0257(89)85035-9.
16. E. Jones, “An Asymptotic Outer Solution Applied to the Keller Box Method,” *Journal of Computational Physics*, 1981, doi: 10.1016/0021-9991(81)90219-9.
17. T. M. A. El-Mistikawy, “Solution of Keller’s Box Equations for Direct and Inverse Boundary-Layer Problems,” *AIAA Journal*, vol. 32, no. 7, 1994, doi: 10.2514/3.12226.
18. J. Buongiorno, “Convective Transport in Nanofluids,” *Journal of Heat Transfer*, vol. 128, no. 3, pp. 240–250, 2006, doi: 10.1115/1.2150834.
19. W. A. Khan and I. Pop, “Boundary-Layer Flow of a Nanofluid Past a Stretching Sheet,” *International Journal of Heat and Mass Transfer*, vol. 53, no. 11–12, pp. 2477–2483, 2010, doi: 10.1016/j.ijheatmasstransfer.2010.01.032.
20. F. Mabood, W. A. Khan, and A. I. M. Ismail, “MHD Boundary Layer Flow and Heat Transfer of Nanofluids over a Nonlinear Stretching Sheet: A Numerical Study,” *Journal of Magnetism and Magnetic Materials*, vol. 374, pp. 569–576, 2015, doi: 10.1016/j.jmmm.2014.09.013.
21. W. Ibrahim and G. Gadisa, “Finite Element Method Solution of Boundary Layer Flow of Powell–Eyring Nanofluid over a Nonlinear Stretching Surface,” *Journal of Applied Mathematics*, vol. 2019, Article ID 3472518, 2019, doi: 10.1155/2019/3472518.
22. S. Hussain, S. E. Ahmed, and T. Akbar, “Finite Element Solution for MHD Flow of Nanofluids with Heat and Mass Transfer through a Porous Media with Thermal Radiation, Viscous Dissipation and Chemical Reaction Effects,” *Advances in Applied Mathematics and Mechanics*, vol. 9, no. 4, pp. 904–923, 2017, doi: 10.4208/aamm.2015.m1031.
23. M. S. Arif, A. Raza, K. Abodayeh, and M. Bibi, “The Modified Finite Element Method for Heat and Mass Transfer of Unsteady Reacting Flow with Mixed Convection,” *Frontiers in Physics*, vol. 10, Article 952787, 2022,

- doi: 10.3389/fphy.2022.952787.
24. Y. Nawaz, M. S. Arif, K. Abodayeh, and M. Bibi, “Finite Element Method for Non-Newtonian Radiative Maxwell Nanofluid Flow under the Influence of Heat and Mass Transfer,” *Energies*, vol. 15, no. 13, Article 4713, 2022, doi: 10.3390/en15134713.
25. M. S. Arif, W. Shatanawi, and Y. Nawaz, “Modified Finite Element Study for Heat and Mass Transfer of Electrical MHD Non-Newtonian Boundary Layer Nanofluid Flow,” *Mathematics*, vol. 11, no. 4, Article 1064, 2023, doi: 10.3390/math11041064.
26. A. Subba Rao, V. R. Prasad, O. A. Bég, and A. Kadir, “Non-Similar Computational Solution for Boundary Layer Flows of Non-Newtonian Fluid from an Inclined Plate with Thermal Slip,” *Journal of Applied Fluid Mechanics*, vol. 9, no. 2, pp. 795–807, 2016, doi: 10.18869/acadpub.jafm.68.225.24664.
27. K. Madhavi, O. A. Bég, and V. R. Prasad, “Heat Transfer Boundary Layer Flow of Jeffrey’s Fluid from a Vertical Isothermal Cone in the Presence of Micro-Polar,” *Frontiers in Heat and Mass Transfer*, vol. 9, Article 29, 2017, doi: 10.5098/hmt.9.29.
28. A. Aziz, “A Similarity Solution for Laminar Thermal Boundary Layer over a Flat Plate with a Convective Surface Boundary Condition,” *Communications in Nonlinear Science and Numerical Simulation*, vol. 14, no. 4, pp. 1064–1068, 2009, doi: 10.1016/j.cnsns.2008.05.003.
29. A. Ishak, R. Nazar, and I. Pop, “Boundary Layer MHD Flow and Heat Transfer over an Unsteady Stretching Vertical Surface,” *Meccanica*, vol. 44, no. 4, pp. 369–375, 2009, doi: 10.1007/s11012-008-9176-9.
30. O. D. Makinde and A. Aziz, “Boundary Layer Flow of a Nanofluid Past a Stretching Sheet with a Convective Boundary Condition,” *International Journal of Thermal Sciences*, vol. 50, no. 7, pp. 1326–1332, 2011, doi: 10.1016/j.ijthermalsci.2011.02.019.
31. N. Bachok, A. Ishak, and I. Pop, “Boundary-Layer Flow of Nanofluids over a Moving Surface in a Flowing Fluid,” *International Journal of Thermal Sciences*, vol. 49, no. 9, pp. 1663–1668, 2010, doi: 10.1016/j.ijthermalsci.2010.01.026.
32. K. Bhattacharyya, “Boundary Layer Stagnation-Point Flow of Casson Fluid and Heat Transfer towards a Shrinking/Stretching Sheet,” *Frontiers in Heat and Mass Transfer*, vol. 4, Article 023003, 2013, doi: 10.5098/hmt.v4.2.3003.
33. T. Hayat, S. Qayyum, M. Imtiaz, and A. Alsaedi, “Impact of Cattaneo–Christov Heat Flux in Jeffrey Fluid Flow with Homogeneous–Heterogeneous Reactions,” *PLOS ONE*, vol. 11, no. 2, Article e0148662, 2016, doi: 10.1371/journal.pone.0148662.
34. L. A. Lund, Z. Omar, I. Khan, and D. Baleanu, “Effect of Viscous Dissipation in Heat Transfer of MHD Flow of Micropolar Fluid Partial Slip Conditions: Dual Solutions and Stability Analysis,” *Energies*, vol. 12, no. 24, Article 4617, 2019, doi: 10.3390/en12244617.
35. M. Ramzan, M. Bilal, J. D. Chung, and U. Farooq, “Heat Transfer Analysis of the Mixed Convective Flow of Magnetohydrodynamic Hybrid Nanofluid with Slip Conditions,” *PLOS ONE*, vol. 16, no. 12, Article e0260854, 2021, doi: 10.1371/journal.pone.0260854.
36. P. Rai and U. Mishra, “Numerical Simulation of Boundary Layer Flow Over a Moving Plate in the Presence of Magnetic Field and Slip Conditions,” *Journal of Advanced Research in Fluid Mechanics and Thermal Sciences*, vol. 95, no. 2, pp. 120–136, 2022, doi: 10.37934/arfmts.95.2.120136.
37. P. Rai and U. Mishra, “Unveiling the Behavior of MHD Mixed Convective Nanofluid Slip Flow over a Moving Vertical Plate with Radiation, Chemical Reaction, and Viscous Dissipation,” *CFD Letters*, vol. 15, no. 10, pp. 93–109, 2023, doi: 10.37934/cfdl.15.10.93109.
38. P. Rai and U. Mishra, “Exploring Dynamic Enhancements in MHD Heat Transfer with Second Order Slip Model in Radiative Fluid Flow through Porous Media along a Stretching Cylinder,” *International Journal of Heat and Technology*, vol. 42, no. 3, pp. 960–980, 2024, doi: 10.18280/ijht.420324.
39. P. Rai and U. Mishra, “Exploring Dual Solutions and Characterisation of Viscous Dissipation Effects on MHD Flow along a Stretching Sheet with Variable Thickness: A Computational Approach,” *International Journal of Computational Fluid Dynamics*, vol. 38, no. 1, pp. 28–44, 2024, doi: 10.1080/10618562.2024.2391798.
40. P. Mathur, P. Rai, A. K. Gupta, and H. M. Singh, “Physics-Informed Neural Network Analysis of Radiative MHD Mixed Convection in Reactive Nanofluid Slip Flow over a Moving Vertical Plate,” *Results in Engineering*, vol. 30, Article 110126, 2026, doi: 10.1016/j.rineng.2026.110126.
41. Rai, P. et al., “Evaluation of Combined Effect of Zero Flux and Convective Boundary Conditions on Magnetohydrodynamic Boundary-Layer Flow of Nanofluid over Moving Surface Using Buongiorno’s Model,” *Engineering Proceedings*, vol. 59, no. 1, Article 245, 2024.
42. P. Rai, P. Mathur, and A. K. Gupta, “Computational analysis of slip-driven MHD two-phase fluid flow in inclined porous fluid channels using the finite element method,” *Int. J. Thermofluids*, vol. 34, Article 101645, 2026, doi: 10.1016/j.ijft.2026.101645.